

Digital Satellite Receiver



LEO-999MATVS



- ALi solution (3329) Biss Key
- Compatible with DVB-S/MPEG-2
- High-quality pictures
- Power Off Memory
- RF modulator (ch2-ch69)
- One port tuner (5039)
- Software can be upgraded
- Box-to-Box upgrading supported
- Highly Reliable Switch Power
- Store 1000 programs (Max.)
- Multi languages (Thailand)
- 9 pictures in one screen function
- DiSEqC 1.2 function

+ Specifications

Tuner

Input Frequency Range	950 ~ 2150 MHz
Input Level	-79 ~ -11dBm
Input Connector	75 ohm. F-Type Female
IF Band Width	27 ~ 36 MHz
LNB Power	13/18V
LNB Tone Switch Control	22KHz Tone / DiSEqC 1.0

Video

Output Format	NTSC/PAL-B/G
Video output Level	1V ± (20mV)p-p
Resolution	720 x 576
Aspect rate	4:3, 16:9
Output type	RCAx3, RFx1

Demodulator

Decode Format	MPEG-2
Symbol Rate	2 ~ 45 Msps
Waveform	QPSK (scpc, mcpc)
Bit Rate	< 15 Mbps

Audio

Frequency Response	20Hz to 20KHz Hi-Fi
Output Type	L/R (2 way)
Sampling Rate	32 / 44.1 / 48 KHz